

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
4 November 2004 (04.11.2004)

PCT

(10) International Publication Number
WO 2004/093952 A1

(51) International Patent Classification: A61M 15/00,
G01F 11/16, 11/02

(21) International Application Number:
PCT/GB2004/000789

(22) International Filing Date: 27 February 2004 (27.02.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data: 0309123.8 22 April 2003 (22.04.2003) GB

(71) Applicant (for all designated States except US): BESPARK
PLC (GB/GB); Bergen Way, North Lynn Industrial Estate,
King's Lynn, Norfolk PE30 2JJ (GB).

(72) Inventor: and

(75) Inventor/Applicant (for US only): THORNHILL, Fris-
tian, Roger (GB/GB); 21 Manor Avenue, Flinton Avenue,
Peterborough, Cambridgeshire PE2 8BZ (GB).


(74) Agents: THOMSON, Neil, David et al.; Boulton Wade
Tennant, Verulam Gardens, 70 Gray's Inn Road, London
WC1X 8BT (GB).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AI, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SI, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,
GB, GR, HU, IE, IT, LU, MC, NL, PT, RO, SE, SI, SK,

[Continued on next page]

(54) Title: DISPENSING APPARATUS



(57) Abstract: The present invention relates to a dispensing apparatus (1) comprising a housing (3) and a metering tube (7). The metering tube (7) has an opening (17) to the interior thereof and the housing (3) has a chamber (4) therein for storing medicament. The metering tube (7) is extendable to a dispensing position, and retractable to a filling position. The opening (17) is in communication with the chamber (4) when the metering tube is in the filling position. The invention further relates to a method of operating dispensing apparatus.

BEST AVAILABLE COPY

WO 2004/093952 A1

WO 2004/093952 A1



TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

Published:

— with international search report

For two letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

x/po/28

Dispensing Apparatus

The invention relates to apparatus for dispensing liquids. More particularly, the invention relates to apparatus for dispensing metered doses of medicaments.

It is known from the Applicant's earlier International application PCT/GB93/02194 to provide dispensing apparatus to deliver a metered dose of liquid from a reservoir. The apparatus described in this application relies, in one embodiment, on one-way valves used in combination with a piston to deliver metered volumes of fluid. However, if an adequate seal is not created by the valve between the piston and the reservoir, fluid may be forced back into the reservoir when the piston is actuated. Thus, the metered dose dispensed may not be accurate.

There remains a need to provide apparatus for accurately dispensing metered doses of medicament. The present invention in preferred embodiments attempts to address this need.

Viewed from a first aspect the present invention provides a dispensing apparatus comprising a housing and a metering tube, said metering tube having an opening to the interior thereof, and said housing having a chamber therein for storing medicament; said metering tube being extendable to a dispensing position, and retractable to a filling position;

wherein said opening is in communication with said chamber when said metering tube is in said filling position.

The retraction of the metering tube into the chamber facilitates the measurement of a metered dose

- 2 -

of medicament to a high degree of accuracy. The extension of the metering tube to the dispensing position facilitating accurate dispensing of the metered dose.

5

After dispensing the medicament, the metering tube may be retracted. Advantageously the surface tension in the dispensed medicament may draw any medicament from the tip of the metering tube so that
10 only a small residue remains. Thus, retracting the metering tube after dispensing the medicament may still further improve the accuracy of the dispensing apparatus. The retraction of the metering tube into the housing also reduces the possibility of it being
15 damaged, or contamination occurring, when the dispensing apparatus is not in use.

The dispensing apparatus preferably comprises a piston for drawing medicament from the chamber into
20 the metering tube when the tube is in the filling position and preferably also to expel medicament from the dispensing apparatus when the tube is in the dispensing position. The medicament is preferably drawn into the indexing tube and expelled through the
25 same opening.

The piston may be mounted remotely from the indexing tube and connected, for example, by a flexible tube to accommodate the movement of the
30 indexing tube. Preferably, however, the piston is moveable with the metering tube to simplify construction. Most preferably, the piston is provided inside said metering tube.

35 Although the length of the piston stroke may be varied to allow different volumes of medicament to be drawn into the metering tube, the stroke length is

- 3 -

preferably fixed so that a predetermined volume of medicament is drawn into the tube from the chamber each time the apparatus is used.

5 In arrangements where the piston is moveable with the indexing tube, at least one member is preferably provided on the metering tube to limit the displacement of the piston in at least one direction.

10 The displacement of the indexing tube relative to the housing is preferably limited, for example by at least one stop provided on the housing and/or the indexing tube, to reduce the likelihood of the indexing tube being damaged in use. The at least one
15 stop is preferably a collar provided on the indexing tube.

 The dispensing apparatus as described herein may be used as part of a hand-held inhaler for oral
20 delivery of medicament. When used in inhalers the apparatus preferably further comprises apparatus for delivering the dispensed medicament as an atomised mist.

25 Viewed from a further aspect the present invention provides a method of operating dispensing apparatus comprising a housing and a metering tube, the housing having a chamber and medicament being provided in said chamber, wherein the method comprises
30 the steps of:

- (a) retracting said metering tube to a filling position;
- (b) drawing medicament into said metering tube from said chamber;
- 35 (c) extending said metering tube to a dispensing position; and
- (d) expelling medicament from said metering tube.

- 4 -

The apparatus preferably further comprises a piston. The movement of the piston in a first direction preferably draws medicament into the metering tube in accordance with step (b) of the method, and movement of the piston in a second direction preferably expels medicament from the metering tube in accordance with step (d) of the method.

10 The piston and the metering tube are preferably moveable together during steps (a) and (c) of the method.

15 The dispensing apparatus may be provided in a hand-held inhaler for oral delivery of medicament. When used in an inhaler, the medicament is preferably dispensed from the metering tube to an atomising apparatus and the method further comprises the step(s) of atomising the medicament and delivering it as an atomised mist.

20 Preferably the metering tube is retracted before the medicament is atomised as the surface tension in the dispensed liquid draws substantially all of the liquid off the tip of the indexing tube, leaving only a small residue.

25 A preferred embodiment of the present invention will now be described, by way of example only, with reference to the accompanying drawings in which:

30 Fig. 1 shows the dispenser in a storage position;
 Fig. 2 shows the dispenser in a charged position;
 Fig. 3 shows the dispenser in an extended position;

35 Fig. 4 shows the dispenser in a discharged position;

- 5 -

Fig. 5 shows an exploded view of the piston and indexing tube assembly;

Fig. 6 shows an exploded view of the indexing tube end cap assembly;

5 Fig. 7 shows an exploded view of the indexing tube and retaining cap assembly;

Fig. 8 shows a partial cross-section of the housing assembly; and

10 Fig. 9 shows a partial cross-section of the dispenser ready for filling.

A dispenser 1 in accordance with the present invention is shown in Fig.1. The dispenser 1 has a housing 3 having a chamber 4 defined therein by a
15 sealing member 5. An O-ring is provided around the sealing member to seal the chamber. A medicament (not shown) to be dispensed is stored in the chamber. A retaining cap 6 is provided on the upper end of the housing to retain the sealing member in position.

20

A metering tube 7 is slidably mounted in the housing 3. An end piece 11 is provided in the metering tube 7 to seal the distal end thereof. An opening 17 is provided in the side wall of the distal
25 end of the metering tube 7 to provide access to the interior thereof. The metering tube extends through a first opening 13 in the housing and a second opening 15 in the sealing member 5. O-rings are provided at each of the first and second openings to seal the
30 chamber 4.

A piston 9 is slidably located in the metering tube 7 and an O-ring 19 is provided at the distal end thereof to create a seal. A handle 21 is provided at
35 the proximal end of the piston to enable a user to displace the piston relative to the metering tube.

- 6 -

An end cap 25 comprising upper and lower members 26, 28 is mounted on the proximal end of the metering tube. A cavity is defined in the end cap between the upper and lower members 26, 28 to receive the handle 21 of the piston 9.

A projection 23 provided at the base of the handle 21 in use limits the length of the piston stroke by abutting the upper and lower end cap members 26, 28 when the piston is displaced. Similarly, a collar 27 integrally formed in the sidewall of the indexing tube 7 abuts the retaining cap 6 and the sealing member 5 to limit the displacement of the tube relative to the housing 3.

The dispenser 1 is typically used in a hand held inhaler for oral inhalation of medicament. To deliver the medicament in an atomised mist for inhalation, the dispenser 1 dispenses the medicament onto an atomising apparatus 29. An atomisation apparatus suitable for use with the present invention is disclosed in the Applicant's earlier UK Patent No. 2240494.

The atomising apparatus 29 comprises a perforated member 31 which is vibrated by an electro-acoustic transducer (not shown) to produce the atomised mist. A trough 33 is provided above the perforated member 31 to receive the medicament dispensed from the dispenser 1.

The operation of the dispenser 1 in accordance with the present invention will now be described with reference to Figs. 1 to 4. The dispenser 1 is stored with the metering tube 7 retracted into the housing ready for filling of the metering tube. In this position the opening 17 is in fluid communication with the medicament in the chamber 4 and this

- 7 -

advantageously ensures that the opening and the interior of the metering tube do not dry out.

5 When the dispenser 1 is in the storage position, the piston 9 is preferably displaced downwardly to minimise the volume of medicament stored inside the metering tube 7 to facilitate thorough mixing of the medicament prior to dispensing.

10 Prior to charging the metering tube, the dispenser 1 is shaken to disperse any particulates in the medicament in the case that the medicament is stored in the form of a suspension. Medicament in the form of a solution does not require agitation prior to
15 charging. With the dispenser in the upright position, as shown in Fig. 1, the plunger 9 is moved upwardly, relative to the metering tube 7. The displacement of the piston relative to the metering tube effectively creates a metering chamber into which a metered dose
20 35 of medicament is drawn via the opening 17.

 The upward displacement of the piston 9 is limited by the projection 23 which abuts the upper portion 26 of the end cap 25. The length of the
25 piston stroke determines the volume of medicament drawn into the metering tube; thus, the metered dose 35 may be varied by changing the piston stroke. The piston stroke may be changed, for example, by
30 inserting spacer rings or shims 37 between the upper and lower portions 26, 26 of the end cap 25, as shown in Fig. 6. Preferably the length of the piston stroke, and thus the volume of the metered dose, is fixed when the dispenser 1 is manufactured.

35 The next stage in the operation of the dispenser 1 is to displace the metering tube 7 and the piston 9 downwardly together, i.e. with substantially no

- 8 -

relative movement therebetween. This action extends the distal end of the metering tube 7 out of the housing 3 to the dispensing position. In the dispensing position the opening 17 is also displaced
5 out of the housing.

Medicament is dispensed from the dispenser 1 by displacing the plunger 9 downwardly to expel the metered dose 35 from the interior of the indexing tube
10 7 through the opening 17. The indexed dose is collected in the trough 33 of the atomising apparatus 29 ready for delivery as an atomised mist. At the end of the piston stroke, the tip of the piston 9 is preferably immersed in the dispensed metered dose.

15 Prior to operation of the atomising apparatus 29, the metering tube 7 is preferably withdrawn and returned to the original storage/filling position. As the metering tube is withdrawn, the surface tension in
20 the dispensed metered dose 35 draws any fluid remaining on the tip of the end member 11 into the trough 33. Thus, only a small residue of medicament may remain on the tip of the metering tube. The atomising apparatus 29 may then be operated in
25 accordance with known practise.

The construction of the dispenser 1 will now be described with reference to Figs. 5, 6 and 7. The O-ring 19 is located on the distal end of the piston 9
30 prior to insertion of the piston into the indexing tube 7, as shown in Fig. 5. The upper portion 26 of the end cap 25 is then screwed onto the lower portion 28 such that a portion of the handle 21, including the projection 23, is located in the cavity defined in the
35 end cap. As shown in Fig. 6, one or more shims 37 may be inserted between the upper and lower portions of the end cap member to vary the stroke of the piston 9,

- 9 -

if required.

5 The indexing tube 7 and piston 9 are then inserted through the retaining cap 6. As shown in Fig.7, a key-hole slot 39 is provided in the retaining cap to facilitate introduction of the collar 27. In use, the collar abuts the retaining cap around the narrower central slot portion of the key-hole slot to limit the displacement of the indexing tube.

10

The indexing tube 7 is then inserted through the opening 15 in the sealing member 5 and the opening 13 in the distal end of the housing 3, as shown in Fig. 8. The retaining cap 6 is then screwed into position on the housing 3 to secure the assembly.

15

20 The method of filling the chamber 4 with medicament or other fluid will now be described with reference to Fig. 9. The dispenser 1 is inverted so that the opening 13 in the distal end of the housing 3 is at the top. The retaining cap 6 is then unscrewed and the collar 27 moved to the other side of the retaining cap. The retaining cap is then screwed back into the housing 3 with the metering tube 7 retained in position in the sealing member 5, but retracted sufficiently to leave the opening 13 in the distal end of the housing 3 unobstructed.

25

30 A syringe with a needle of approximately 1 mm diameter is then inserted through the opening 13 into the housing 3 and the required amount of fluid injected through the opening into the chamber 4.

35

The volume injected into the chamber 4 should leave at least 15% of the internal volume of the chamber unfilled in order to facilitate agitation of the fluid by shaking to disperse solid particles. The

- 10 -

charge volume of the chamber 4 may be, for example, 5.1 ml.

5 After the liquid has been injected into the chamber 4, the retaining cap 6 is again unscrewed and the collar 27 of the metering tube 7 moved through the key hole-slot 37 to the inside of the retaining cap. The retaining cap is then screwed back into position.

10 Although the dispenser 1 in accordance with the present invention has been described for use in conjunction with atomising apparatus 29, the skilled person will appreciate that the dispenser may equally be used for other applications where the accurate
15 dispensing of a metered dose of medicament is required. Indeed, the skilled person will appreciate that the dispenser may be used in any application required dispensing of a fluid and is not limited to dispensing of medicaments.

20

- 11 -

CLAIMS:

1. A dispensing apparatus comprising a housing and a metering tube, said metering tube having an opening to the interior thereof and said housing having a chamber therein for storing medicament;
said metering tube being extendable to a dispensing position, and retractable to a filling position;
wherein said opening is in communication with said chamber when said metering tube is in said filling position.
2. Dispensing apparatus as claimed in claim 1 further comprising a piston for drawing medicament into said metering tube and expelling medicament from said metering tube.
3. Dispensing apparatus as claimed in claim 2 wherein the length of the piston stroke is fixed.
4. Dispensing apparatus as claimed in claim 2 or 3 wherein at least one member is provided on said metering tube to limit the displacement of the piston in at least one direction.
5. Dispensing apparatus as claimed in any one of claims 2 to 4 wherein the piston is provided inside said metering tube.
6. Dispensing apparatus as claimed in any one of claims 2 to 5 wherein said piston is moveable with said metering tube.
7. Dispensing apparatus as claimed in any preceding claim wherein at least one stop is provided to limit the displacement of the metering tube.

- 12 -

8. Dispensing apparatus as claimed in any one of the preceding claims wherein the dispensing apparatus is provided in a hand-held inhaler for oral delivery of medicament.

5

9. Dispensing apparatus as claimed in any one of the preceding claims further comprising apparatus for delivering the dispensed medicament as an atomised mist.

10

10. A method of operating dispensing apparatus comprising a housing and a metering tube, the housing having a chamber and medicament being provided in said chamber, wherein the method comprises the steps of:

15

(a) retracting said metering tube to a filling position;

(b) drawing medicament into said metering tube from said chamber;

20

(c) extending said metering tube to a dispensing position; and

(d) expelling medicament from said metering tube.

25

11. A method as claimed in claim 10 wherein said apparatus further comprises a piston, wherein movement of the piston in a first direction draws medicament into the metering tube in accordance with step (b), and movement of the piston in a second direction expels medicament from the metering tube in accordance with step (d).

30

12. A method as claimed in claim 11 wherein the piston and the metering tube are moved together during steps (a) and (c).

35

13. A method as claimed in any one of claims 10 to 12 wherein the medicament is dispensed from the metering tube to an atomising apparatus and the method further

- 13 -

comprises the step(s) of atomising the medicament and delivering it as an atomised mist.

14. A method as claimed in claim 13 wherein the
5 metering tube is retracted before the medicament is atomised.

15. A method as claimed in any one of claims 11 to 14
10 wherein the dispensing apparatus is provided in a hand-held inhaler for oral delivery of medicament.

16. Dispensing apparatus substantially as described herein with reference to the attached Figures.

15 17. A method of using dispensing apparatus substantially as described herein with reference to the attached Figures.

1/4




FIG. 1




FIG. 2




FIG. 3




FIG. 4

3/4




FIG. 5




FIG. 6




FIG. 7

4/4




FIG. 8




FIG. 9

INTERNATIONAL SEARCH REPORT

PCT/GB2004/000789

A. CLASSIFICATION OF SUBJECT MATTER IPC 7 A61M15/00 G01F11/16 G01F11/02		
According to International Patent Classification (IPC) or to both national classification and IPC		
B. FIELDS SEARCHED Minimum documentation searched (classification system followed by classification symbols) IPC 7 A61M G01F G01B		
Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched		
Electronic data base consulted during the international search (name of data base and, where practical, search terms used) EPO-Internal, WPI Data, PAJ		
C. DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	WO 02/26299 A (SCHUCKMANN ALFRED VON) 4 April 2002 (2002-04-04) page 6, line 195 -page 19, line 641 figures	1,7-9
X	US 4 394 941 A (RECINE GIUSEPPE) 26 July 1983 (1983-07-26) column 1, line 5-10 column 2, line 16 -column 4, line 11 figures	1
A		2-6
X	US 3 049 269 A (ALAN GAWTHROP) 14 August 1962 (1962-08-14) the whole document	1,9
X	US 1 233 791 A (KAISER CHARLES) the whole document	1
-/-		
<input checked="" type="checkbox"/> Further documents are listed in the continuation of box C. <input checked="" type="checkbox"/> Patent family members are listed in annex.		
* Special categories of cited documents: 'A' document defining the general state of the art which is not considered to be of particular relevance 'E' earlier document but published on or after the international filing date 'L' document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified) 'O' document referring to an oral disclosure, use, exhibition or other means 'P' document published prior to the international filing date but later than the priority date claimed 'T' later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention 'X' document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone 'Y' document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art 'Z' document member of the same patent family		
Date of the actual completion of the international search 18 May 2004		Date of mailing of the international search report 02/06/2004
Name and mailing address of the ISA European Patent Office, P.B. 5518 Patentkaser 2 NL - 2280 HV Rijswijk Tel: (+31-70) 340-2040, Tr. 37 661 epo nl, Fax: (+31-70) 340-2016		Authorized officer Azaizia, M

INTERNATIONAL SEARCH REPORT

PCT/GB2004/000789

C. (Continuation) DOCUMENTS CONSIDERED TO BE RELEVANT		
Category *	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
A	GB 1 025 245 A (MERCK & CO INC) 6 April 1966 (1966-04-06) page 4, line 2 -page 5, line 2 page 5, line 84 -page 6, line 54 figures	1,7-9
A	WO 93/02729 A (HABLEY MEDICAL TECHNOLOGY CORP) 18 February 1993 (1993-02-18) the whole document	1-9
A	FR 2 727 670 A (OREAL) 7 June 1996 (1996-06-07) the whole document	1-9
A	US 2002/017536 A1 (BONNINGUE PHILIPPE) 14 February 2002 (2002-02-14) the whole document	1-9

FURTHER INFORMATION CONTINUED FROM PCT/ISA/ 210

Continuation of Box II.2

Claims Nos.: 16,17

Claims 16 and 17 rely, in respect of the technical features of the invention, on references to the description or drawings (Rule 6.2 (a) PCT). The subject-matter of these claims is therefore so unclear that a meaningful search is impossible (Article 6 PCT).

The applicant's attention is drawn to the fact that claims, or parts of claims, relating to inventions in respect of which no international search report has been established need not be the subject of an international preliminary examination (Rule 66.1(e) PCT). The applicant is advised that the EPO policy when acting as an International Preliminary Examining Authority is normally not to carry out a preliminary examination on matter which has not been searched. This is the case irrespective of whether or not the claims are amended following receipt of the search report or during any Chapter II procedure.

INTERNATIONAL SEARCH REPORT

PCT/GB2004/000789

Box II Observations where certain claims were found unsearchable (Continuation of item 2 of first sheet)

This International Search Report has not been established in respect of certain claims under Article 17(2)(a) for the following reasons:

1. ☒ Claims Nos.: 10-15
because they relate to subject matter not required to be searched by this Authority, namely:
Rule 39.1(iv) PCT - Method for treatment of the human or animal body by therapy
2. ☒ Claims Nos.: 16, 17
because they relate to parts of the International Application that do not comply with the prescribed requirements to such an extent that no meaningful International Search can be carried out, specifically:
see FURTHER INFORMATION sheet PCT/ISA/210
3. ☐ Claims Nos.:
because they are dependant claims and are not drafted in accordance with the second and third sentences of Rule 6.4(a).

Box III Observations where unity of invention is lacking (Continuation of item 3 of first sheet)

This International Searching Authority found multiple inventions in this international application, as follows:

1. ☐ As all required additional search fees were timely paid by the applicant, this International Search Report covers all searchable claims.
2. ☐ As all searchable claims could be searched without effort justifying an additional fee, this Authority did not invite payment of any additional fee.
3. ☐ As only some of the required additional search fees were timely paid by the applicant, this International Search Report covers only those claims for which fees were paid, specifically claims Nos.:
4. ☐ No required additional search fees were timely paid by the applicant. Consequently, this International Search Report is restricted to the invention first mentioned in the claims; it is covered by claims Nos.:

Remark on Protest

- ☐ The additional search fees were accompanied by the applicant's protest.
- ☐ No protest accompanied the payment of additional search fees.

INTERNATIONAL SEARCH REPORT

Information on patent family members

PCT/GB2004/000789

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
WO 0226299	A	04-04-2002	DE 10047722 A1	11-04-2002
			AU 8988201 A	08-04-2002
			WO 0226299 A1	04-04-2002
			EP 1320396 A1	25-06-2003
			US 2004035421 A1	26-02-2004
US 4394941	A	26-07-1983	NONE	
US 3049269	A	14-08-1962	GB 878409 A	27-09-1961
US 1233791	A		NONE	
GB 1025245	A	06-04-1966	US 3157179 A	17-11-1964
			DE 1287260 B	16-01-1969
			FR 1374533 A	09-10-1964
			NL 297349 A	
			SE 317467 B	17-11-1969
WO 9302729	A	18-02-1993	WO 9302729 A1	18-02-1993
FR 2727670	A	07-06-1996	FR 2727670 A1	07-06-1996
US 2002017536	A1	14-02-2002	FR 2809088 A1	23-11-2001
			CA 2348105 A1	19-11-2001
			EP 1156300 A1	21-11-2001
			JP 3462862 B2	05-11-2003
			JP 2002087478 A	27-03-2002

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☐ FADED TEXT OR DRAWING
- ☒ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☐ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☒ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.